

GWS

www.gws.com.tw
www.gwsus.com

S35 Servo for Industrial and Robotic Applications

S35 / S35T are specially designed for industrial
and robotic uses. Feature continuous rotation,
linear output, and proportional variable speed control.



High Torque

Superb Design

Super Reliable

High Resolution

Fast Speed



Size:(L)39.5×(W)20.0×(H)35.6/39.5mm



Item	Weight		4.8V				6.0V			
	Gram	Oz.	RPM	Speed SEC/360°	Speed SEC/60°	Torque	RPM	Speed SEC/360°	Speed SEC/60°	Torque
S35	41	1.45	37	1.620	0.270	4.1	45	1.330	0.220	5.0
S35 F	41	1.45	50	1.200	0.200	3.6	61	0.980	0.163	4.3
S35 XF	41	1.45	57	1.050	0.175	2.8	73	0.820	0.137	3.3
S35+	41	1.45	45	1.330	0.220	5.9	53	1.130	0.189	6.8
S35+ F	41	1.45	53	1.130	0.189	4.8	65	0.920	0.153	6.0
S35+ XF	41	1.45	63	0.950	0.158	3.9	79	0.760	0.127	5.1
S35T	46	1.62	27	2.220	0.370	7.7	34	1.760	0.293	8.6
S35T F	46	1.62	32	1.870	0.311	6.9	40	1.500	0.250	7.7
S35T XF	46	1.62	41	1.460	0.243	6.0	51	1.170	0.195	6.9

S35 have optional model 2BB (2 ball bearings), MG (metal gear w/2 ball bearings)
to choose from.